STAR COOPERATION®

Your Partners in Excellence

SENSOR- / ACTUATOR TECHNOLOGY

ENERGY TECHNOLOGY

NETWORK TECHNOLOGY

FlexMedia 100BASE-T1

www.star-cooperation.com

The FlexMedia 100BASE-T1 is a converter for 100BASE-T1 to 100BASE-TX and vice versa. With the FlexMedia 100BASE-T1, it is possible to connect an automotive Ethernet network to a standard PC for testing or diagnostic purposes. It supports up to 100 Mbit/s in full duplex mode on both sides.

BENEFITS

- Master and slave mode selectable via DIP-switch
- Broadcom BCM89810 transceiver is used for the 100BASE-T1 conversion
- Supply voltage: 8-48V DC
- Status LEDs
- RJ45 connector for 100BASE-TX
- D-Sub 9 pin male connector for 100BASE-T1
- IP20
- Temperature range -40°C to +85°C

HARDWARE

Electrical characteristics

Supply voltage			
	Min.	Typ.	Max.
Operating	+8.0 V	-	+48.0 V
Absolut maximum (non-operating)	-60.0 V	-	+60.0 V
Supply current - operating	-	80 mA	

Physical characteristics

Connectors	RJ45, D-Sub 9
Weight approx.	145 g
Dimensions approx. L x W x H	92 x65 x 28 mm

Environmental conditions

Temperature	Operating / Storage:	-40°C to +85°C
Relative humidity	0% – 90% r. H., non-condensing	

SCOPE OF DELIVERY

FlexMedia 100BASE-T1

ORDER INFORMATION FLEXMEDIA 100BASE-T1

Product	Description	Order number
FlexMedia 100BASE-T1	Media converter for 100BASE-T1 to 100BASE-TX and vice versa.	3-V0930A01

All rights reserved. Version 02 - 04/2020 © STAR COOPERATION

STAR COOPERATION GmbH | Otto-Lilienthal-Straße 5 | 71034 Böblingen | Phone +49 7031 6288-300 | elektronik.star-cooperation.com | sales-ee@star-cooperation.com

STAR COOPERATION is certified according to the standards DIN EN ISO 50001:2011, ISO 9001:2015 and ISO 14001:2015. All information is for product information purposes only and does not constitute a claim for warranty regarding the correctness or completeness of the contents. Subject to change without notice.